

Metal cylindrical shape inductive sensors **LR04Q** series


Features

- ◆ Extended sensing distance;
- ◆ ASIC design, safe and reliable;
- ◆ Perfect choice for metallic target detection;


Part number

NPN NO	LR04QAF15DNOY-E1	PNP NO	LR04QAF15DPOY-E1
NPN NC	LR04QAF15DNCY-E1	PNP NC	LR04QAF15DPCY-E1

Technical specifications

Mounting	Flush	Leakage current [I _r]	≤10mA
Rated distance [S _n]	1.5mm	Circuit protection	Reverse polarity
Assured distance [S _a]	0...1.2mm	Output indicator	Red LED
Dimensions	Φ4*54mm	Ambient temperature	-25°C...70°C
Output	NO/NC(depends on part number)	Ambient humidity	35-95%RH
Supply voltage	10...30 VDC	Switching frequency [F]	1200Hz
Standard target	Fe 5*5*1t	Voltage withstand
Switch-point drifts[%/S _r]	≤±10%	Insulation resistance	≥50MΩ (500VDC)
Hysteresis range [%/S _r]	1...20%	Vibration resistance	10...50Hz (1.5mm)
Repeat accuracy [R]	≤3%	Degree of protection	IP67
Load current	≤100mA	Housing material	Stainless steel
Residual voltage	≤2.5V	Connection type	M8 connector

Dimensions



Wiring diagram

